

SmartFill

DataSheet



Smartfill GEN 3

Features

- Simple, secure connection over 3G/4G network or Ethernet connection (NBN broadband)
- Designed for tank mounting or free standing (using optional pedestal)
- Connects to range of pumps – Compac, Gallagher, Gilbarco, Wayne and other popular brands
- Direct pump control for bulk fuelling and applications where a bowser is not used
- Full support for automatic tank gauging systems including SmartDip
- Ability to send SMS receipts
- Easy to use large graphical user interface
- Change pump prices remotely
- UPS, so transactions are not lost on a power failure
- Supports LCR (least cost routing) - minimising merchant fees

Specifications

Size and Weight	Height: 700mm Width: 400mm	Depth: 200mm Weight: 25kg
Display	7" Blankview TFT LCD Display	
Printer	Thermal Printer, 58mm-60mm wide roll	
Payment Hardware	Ingenico Self/5000 Payment Terminal, PCI PTS 5.x compliant	
Payment Acceptance	VISA, MasterCard, AMEX, Account/White Cards (Optional), SmartFill NFC cards and fobs, Apple Pay and Google Pay	
Power and Battery	90 VAC (0.38A) – 250 VAC (0.15A), Battery 24V 29WH	
Supported Fuel Pumps	Compac, Gilbarco, Gallagher, TT, Wayne and other popular brands	
Communications	3G/4G Cellular or wired Ethernet	
Operating Temperature	-40°C to 55°C	
Mounting Options	Tank or Wall Mounted (kit provided). Optional pedestal available	
Construction	316 Grade Stainless Steel	
Installation Requirement	To be installed in non-hazardous zones as defined in AS-NZ-60079.10.1-2009 Explosive atmospheres – Classification of areas	